

(AN-130U1 Back Panel Shown)



MODELS

AN-130 Powered monitor speaker

AN-130CG AN-130 w/ black finish AN-130DC AN-130 w/ 12 volt DC output

ACCESSORIES

MIC-90P Professional dynamic, cardioid pattern handheld mic w/ 1/4" phone plug SS-250 Speaker stand MSB-201 Combination mic/speaker stand SB-1 Swivel stand mounting bracket HS-1 Carry handle CC-100 Storage bag HC-1550 Custom traveling hard case

DELS

AN-130RC AN-130 w/ remote control for volume & mute

AN-130U1 AN-130 w/ UHF wireless receiver with 16 user-selectable channels & remote (order mic separately)

WIRELESS MICS

WH-6000 Handheld wireless microphone/ transmitter WB-6000 Wireless body-pack transmitter (order mic separately) CM-60

CollarMic microphone for use with WB-6000 transmitter HBM-60 Headband microphone for use with WB-6000 transmitter LM-60 Lapel microphone for use with WB-6000 transmitter

MADE IN THE USA!

Now featuring 16 channel UHF diversity wireless by Anchor Audio

Reach crowds of 100+

Delivers up to 101 dB of clear sound

Bass and Treble controls

30 watt amplifier provides lots of sound

Magnetically shielded carbon fiber speaker

Has mic, instrument and 2 line inputs

Durable injection-molded polypropylene case

Weighs just 8.5 pounds

2-way speaker system combines 4.5" woofer and dome tweeter

6-YEAR WARRANTY!

SPECIFICATIONS

(310) 784-2300 • www.anchoraudio.com

AN-130

Rated power: Sensitivity for rated output Line: Microphone: Instrument: Frequency response: Max SPL @ rated power: Line inputs (2):

Mic Input: Instrument Input: AC power requirements: (internally configurable)

Dimensions (HWD): Weight:

30 watts continuous

-20 dBV (100 mVrms) -43 dBV (7.5 mVrms) -30 dBV (30 mVrms) 65 Hz – 18 kHz 101 dB @ 1 meter Hi-Z, unbalanced, dual RCA jacks (summing L+R) Lo-Z, unbalanced, 1/4"-phone (3k), unbalanced, 1/4"-phone 110-125 VAC 50/60 Hz 210-240 VAC 50/60 Hz (50 watts max) 5.25 x 8.4 x 9", 13 x 21 x 23 cm 8.5 lbs, 3.8 Kg

